

AC/DC 24V

Condition		
Environment	Storage Temp.	-25 ~ +75°C
	Ambient Temp.	-25 ~ +55°C
	Relative humidity	45 ~ 85% RH
Lampholder Size		BA15S
Consumed Power	1 Stage	0.5W
	2 Stage	1.0W
	3 Stage	1.5W
	4 Stage	2.0W
	5 Stage	2.5W
	Buzzer	1W
Rated Insulation Voltage		250V
Insulation Resistance		Over 100MΩ
Voltage Range		0.85 ~ 1.10 times Rated Voltage
Buzzer	Sound Volume	90dB at 1m
Characteristic	Wire Range	UL 1007 AWG22

Specyfikacja 24 V

AC220V		
Condition		
Environment	Storage Temp.	-25 ~ +75°C
	Ambient Temp.	-25 ~ +55°C
	Relative humidity	45 ~ 85% RH
Lampholder Size		BA15S
Consumed Power	1 Stage	4W
	2 Stage	8W
	3 Stage	12W
	4 Stage	16W
	5 Stage	20W
	Buzzer	2W
Rated Insulation Voltage		250V
Insulation Resistance		Over 100MΩ
Voltage Range		0.85 ~ 1.10 times Rated Voltage
Buzzer	Sound Volume	90dB at 1m
Characteristic	Wire Range	UL 1007 AWG22

Specyfikacja 220 V

AC/DC 24V

Condition		
Environment	Storage Temp.	-25 ~ +75°C
	Ambient Temp.	-25 ~ +55°C
	Relative humidity	45 ~ 85% RH
Lampholder Size		BA15S
Consumed Power	1 Stage	0.5W
	2 Stage	1.0W
	3 Stage	1.5W
	4 Stage	2.0W
	5 Stage	2.5W
	Buzzer	1W
Rated Insulation Voltage		250V
Insulation Resistance		Over 100MΩ
Voltage Range		0.85 ~ 1.10 times Rated Voltage
Buzzer	Sound Volume	90dB at 1m
Characteristic	Wire Range	UL 1007 AWG22

Specyfikacja 110 V

Wiring Diagram / 接線圖

