

## Model Designation

# AC203A5-S1A0

1 2 3 4 5 6 7 8

### 1-Air Conditioning

Air Conditioning, Heating,  
Lighting

### 2-Full Load Amps

20 = 20 FLA  
25 = 25 FLA  
30 = 30 FLA  
40 = 40 FLA  
50 = 50 FLA

### 3-Number of Poles:

1 = 1 Pole + 1 Shunt  
2 = 2 Pole  
3 = 3 Pole  
4 = 4 Pole  
5 = 1 Pole  
6 = 3ø-2Pole

### 4-Coil Voltage

Coil Voltage	24V	48V	110V	120V	190V	220V	230V	240V	380V	415V	440V	480V	277V	600V
50Hz	A5	C5	D5	E5	F5	G5	H5	I5	J5	L5	M5	N5	W5	Q5
60Hz	A6	C6	D6	E6	F6	G6	H6	I6	J6	L6	M6	N6	W6	Q6

### 5.-Mounting Plate:

R = Dine Rail  
S = Standard Mounting

### 6.-Main Terminals:

1 = Screw  
2 = Screw with quick connect  
3 = Box Lug  
4 = Box Lug with quick connect

### 7.-Coil Terminals:

A = 6.35 mm ( .250" ) quick connect on the same side in 3 and 4 pole models.  
B = 6.35 mm ( .250" ) quick connect on the opposite side in 1,2 and 3 pole models.  
C = Dual terminals with screw on the same side in 3 pole models.  
D = Dual terminals with screw on the opposite side in 2 and 3 pole models.

### 8.-Power Quick Terminals

Blank = Dual terminals in 1 and 2 pole models. Dual terminals in 3 and 4 pole models.  
0 = Without any terminals.  
1 = Terminals on line side only.  
2 = Terminals on load side only.  
3 = Dual terminals in 1 and 2 poles.